9110 Utensil Washer **Technical Specifications**

JEROS 9110 Features:

- Top & Bottom Spray Bars
- 3-side Open Design \checkmark
- Ergonomic Loading and Unloading
- **3 Programmable Wash Cycle Buttons**
- Environmentally Friendly
- **Built-in Soap Dosing Systems**
- Self-contained Wash Water Heating Elements
- Adjustable Wash Temperature
- Separate Sanitary Rinse Plumbing
- ✓ Built-in 184 °F Rinse
- ✓ Adjustable Rinse Temperature
- "Rinse Sense" Guaranteed Sanitation
- **Minimal Space Requirement**
- Automatic Start
- Automatic Drain and Rinse System
- 17 PSI of Pressure at the Nozzle
- Easily Accessible Waste Collection Basket
- \checkmark High and Low Pressure Wash Program
- \checkmark **NSF** Approved

Options:

- **Chemical Sanitation Pump**
- **Integrated Faucet**
- Pre-spray Nozzle and Hose
- **External Pre-wash Hose**

General Specifications:

Wash Tank Capacity	13.4 gallons (50.72 liters)
Wash Area	27" W x 25" D x 23" H
Overall Dimensions	
Hood Closed	33" W x 33.5" D x 64" H
Hood Open	33" W x 33.5" D x 83" H
Includes Cord (no plug)	

Wash, Rinse and Sanitize in as little as 3 minutes... "If it FITS INSIDE – It's SANITIZED"





POWER / UTILITIES

Electrical:

Electrical Connection Total Amperage Heating Elements: Wash Tank **Rinse Tank** Wash Pump Motor

3 ph, 60Hz, 230/480 volt 34 amp (at 230 v)

NSF

Water:

Connection Input Pressure Required Water Consumption per Cycle Input Temperature (minimum) **Rinse Temperature Rinse Time**

Drain: **Drain Diameter** 45 to 60 psi 1 gallon (3.8 liters) 122 °F (50 °C) 180° - 203 °F (82° - 95 °C) 20 - 40 seconds

1-1/2" (8' Flex drain incl'd)

1 x 4.5 kW 2 x 6.0 kW

1 HP, 5.0 kW 1/2" NPT Flex